

B21

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : G01N 21/88	A1	(11) International Publication Number: WO 99/31490 (43) International Publication Date: 24 June 1999 (24.06.99)
(21) International Application Number: PCT/US98/23348 (22) International Filing Date: 2 November 1998 (02.11.98)  (30) Priority Data: 08/990,462 15 December 1997 (15.12.97) US  (71) Applicant: APPLIED MATERIALS, INC. [US/US]; 3050 Bowers Avenue, Santa Clara, CA 95054 (US). (72) Inventor: ALMOGY, Gilad; Apartment 6, Poalei Harekevet Street 8, 83257 Givataim (IL). (74) Agents: BERNADICOU, Michael, A. et al.; Blakely, Sokoloff, Taylor & Zafman LLP, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US).		(81) Designated States: JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published With international search report.

(54) Title: MULTIPLE BEAM SCANNER FOR AN INSPECTION SYSTEM

## (57) Abstract

An inspection system using dark field imaging includes a multiple beam laser scanning unit and at least one multiple beam dark field imaging unit. The laser scanning unit generates multiple beams which illuminate multiple spots on a surface to be scanned. The imaging unit separately detects light scattered from the multiple spots. The spots are separated by a separation distance which ensures that scattered light from each associated spot are received only by its associated photodetector. Each imaging unit includes collection optics and multiple photodetectors, one per spot. The collection optics and photodetectors are mounted so as to separate the light scattered from the different scan lines. In one embodiment, this separation is provided by arranging the collection optics and photodetectors according to the principles of Scheimpflug imaging.



133

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## MULTIPLE BEAM SCANNER FOR AN INSPECTION SYSTEM

### FIELD OF THE INVENTION

5       The present invention relates to laser scanning in general and to laser scanning within inspection systems in particular.

### BACKGROUND OF THE INVENTION

Laser scanning involves moving a laser beam along a surface to be scanned and can be used for both writing and reading purposes. For example,  
10   laser scanning is used for writing in printing systems, where the scanned beam activates spots on a printing medium, and in cutting systems where the scanned beam cuts material. For reading, laser scanning is used in inspection systems and in copiers which use the scanned beam to illuminate consecutive spots of a surface to be viewed or a page to be copied.

15       Fig. 1, to which reference is now made, schematically illustrates a laser scanning system for printing and a surface 10 of a medium to be activated. The system includes a laser 12, a pre-scan optical system 16, a scan unit 14, and a post-scan optical system 20. The scan unit 14 can be an acousto-optic deflector, a polygon deflector a hologon deflector or an oscillating mirror.

20       The laser 12 produces a beam 22, the pre-scan optical system 16 provides the scanned beam with the desired optical properties and the scan unit 14 deflects the beam 22 to provide the scanning motion, as indicated by arrow 24. The post-scan optical system 20 focuses the scanned beam on the

medium 10, thereby to produce the printing spot, and converts the angular scan of arrow 24 to a linear scan, as indicated by arrow 26.

Due to the action of the scan unit 14, the focused beam scans a portion of the medium 10, as indicated by arrow 26, in one direction, known as the "fast scan direction". The medium 10 typically is moved, as indicated by arrow 28, in a second direction, orthogonal to the fast scan direction. This is generally known as the slow scan direction. The fast and slow scan directions together provide two-dimensional scanning. Alternatively, the scan unit 14 can produce two-dimensional scanning if it includes means for deflecting the beam along a second direction.

The scanning rate (defined as pixels/sec or spots/sec) of any laser scanning system is a function of the velocity of the spot and the size of the spot, both of which are functions of the limitations of the scan unit. The scanning rate is thus limited by the fundamental parameters and quality of the scan unit. It will be appreciated that, for a given pixel or spot size, the scanning rate determines the throughput (e.g. number of pages printed or number of wafers inspected within a given period of time).

It is known to increase the throughput of a laser scanning system for printing by increasing the number of beams being scanned at one time. One such system, with 32 beams, is the ALTA-3500, commercially available from Etec Systems Inc. of California, USA.

Fig. 2, to which reference is now briefly made, schematically shows the system, but with only three beams 30. The multiple beams can be aligned along the fast scan direction, as shown, or along the slow scan direction. A

beam generating unit 32, such as multiple lasers or a single laser with multiple beam splitters, produces the multiple beams 30. The multiple beams 30 pass through a system similar to that shown hereinabove for Fig. 1 but whose elements are designed for multiple beams. Thus, the scan unit and pre- and  
5 post-optical systems carry similar reference numerals as those of the scanning system of Fig. 1 but are additionally marked with an apostrophe (').

The multiple processed beams, labeled 34, are scanned along the surface of the medium 10, thereby generating multiple parallel scan lines at one time. This typically increases the throughput of the scanning system by the  
10 number N of beams used, where an N of two to many hundreds are known.

Laser scanning systems for inspection systems utilize the scanned light for illumination of an article to be inspected by one or more detectors. Such a system is shown schematically in Fig. 3, to which reference is now made. Like the previous scanning systems, it also includes laser 12, scan unit 14, pre-scan  
15 optical system 16 and post-scan optical system 20. However, the inspection system also includes multiple light detectors 40 for detecting the shape of features on a surface 42, such as the surface of a semiconductor wafer, from different viewing perspectives. The movement of the surface 42 is indicated by arrow 44.

20 The scanning elements illuminate the surface 42 from above and the surface 42 scatters the light in many directions, as a function of the optical characteristics of the features thereon. The inspection system of Fig. 3 is a "dark field" inspection system since its detectors 40 collect the light scattered

from the surface 42 at an oblique angle  $\beta$  which is outside of the convergence angle of the post-scan optical system 20.

The oblique angle  $\beta$  varies depending on the type of surface to be inspected and the type of features to be inspected. The light detectors 40 are  
5 typically non-imaging detectors, such as a photomultiplier tubes, which measure the changing intensity, over time, of the light impinging upon them. As is known to those skilled in the art, in order to differentiate the light from different pixels on the surface 42, the signal from the photomultiplier tube must be sampled at a rate corresponding to the spot size and to the velocity of the  
10 spot on the surface 42. This may be called "temporal resolution".

As in the other scanning systems, the scanning rate of the inspection system of Fig. 3 is a function of the fundamental parameters and the quality of the scan unit 14. Of course, as in other scanning systems, it is desirable to increase the scanning rate of the inspection system. However, an inspection  
15 system does not easily lend itself to operating with multiple beams. One reason is that non-imaging detectors do not discern the position from which the light was scattered. Adding other beams would, therefore, cause cross-talk on the detectors caused by the signals from the other spots. Imaging detectors cannot easily be incorporated into a dark field imaging system since, due to oblique  
20 incidence angle  $\beta$ , the collection optics cannot resolve sufficiently small pixels such as is possible with detectors placed at a non-oblique angle.

## SUMMARY OF THE INVENTION

An object of the present invention is to provide multiple scanning beams within an inspection system.

There is therefore provided, in accordance with a preferred  
5 embodiment of the present invention, an inspection system using at least dark field imaging which includes a multiple beam laser scanning unit and at least one multiple beam dark field imaging unit. The laser scanning unit generates multiple beams which illuminate multiple spots on a surface to be scanned. Each imaging unit collects light from one viewing perspective and separately  
10 detects light scattered from the multiple spots.

Moreover, in accordance with a preferred embodiment of the present invention, each imaging unit includes a plurality of photodetectors, at least one per spot, spaced apart from each other and collection optics directing light scattered from each spot to an assigned one of the photodetectors.

15 In one embodiment, the collection optics and photodetectors are arranged according to the principles of Scheimpflug imaging. For example, the collection optics are mounted so that the longitudinal axis of its thin lens equivalent is at a first non-parallel angle to the surface, the multiple photodetectors are mounted along an image plane of the collection optics and  
20 the image plane is at a second non-parallel angle to the longitudinal axis.

Additionally, in accordance with a preferred embodiment of the present invention, the collection optics may include a spatial filter which limits the range of angles of scattered light which are received by the multiple photodetectors.

The limiting unit can be an aperture stop. The collection optics can also include wavelength filters and/or polarization filters.

Further, in accordance with a preferred embodiment of the present invention, the multiple beams are separated by a separation distance which  
5 ensures that light scattered from each associated spot is received only by its associated photodetector. In one embodiment, the separation distance is generally a multiple K of the length of a scan row less an overlap amount. K can be two. The present invention incorporates other separation distances.

Finally, there is provided an inspection system using dark field imaging  
10 which includes a sensor unit which spatially separates between multiple scan lines scanned at generally the same time and which temporally separates pixels within the multiple scan lines.



**BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the appended drawings in which:

5           Fig. 1 is a schematic illustration of a prior art laser scanning system for printing;

          Fig. 2 is a schematic illustration of a prior art laser scanning system for printing which uses multiple beams;

          Fig. 3 is a schematic illustration of a prior art laser scanning system for  
10   inspection;

          Fig. 4 is a schematic illustration of a laser scanning system for inspection which uses multiple beams;

          Fig. 5 is a schematic illustration of the scanning motions of the system of Fig. 4; and

15           Fig. 6 is a schematic illustration of a spatial filter within the inspection system of Fig. 4.

## DETAILED DESCRIPTION OF THE PRESENT INVENTION

Reference is now made to Figs. 4 and 5 which illustrate the present invention. Fig. 4 illustrates a multiple beam laser scanning system 50 and one multiple beam imaging system 52 per perspective. Fig. 5 illustrates the scan pattern upon a surface to be scanned, such as the surface 54 of a semiconductor wafer.

As in the prior art, the multiple beam laser scanning system 50 comprises a beam generating unit 56, such as multiple lasers or a single laser with multiple beam splitters, one or more scan units 58, a pre-scan optical system 60 and a post-scan optical system 64.

Scanning system 50 scans multiple beams across the surface 54, either one- or two-dimensionally. In the former case, the surface 54 is moved in the second direction.

Two exemplary beams, labeled 70A and 70B, are shown. It will be appreciated that the present invention is operative for two or more beams and that the two shown are for clarity only.

Each multiple beam imaging system 52 comprises collection optics 74 and multiple photodetectors 76, one per spot. Fig. 4 shows one imaging system 52 with two photodetectors, labeled 76A and 76B, which, via collection optics 74, receive the light scattered from the surface 54 when beams 70A and 70B, respectively, impinge thereupon.

Collection optics 74 can be a single lens or multiple optical components, as necessary for the particular application. The discussion hereinbelow will describe the optical qualities of collection optics 74 as though

collection optics 74 were a single, thin lens, to be called herein the "collection lens 74". This is known as the "thin lens equivalence".

Collection lens 74 is placed such that its longitudinal axis, labeled 78, is perpendicular to a center line 80 which is at the oblique angle  $\beta$  to the object surface 54. Line 80 extends along angle  $\beta$  from a center point 81 of the scanned beams 70, where center point 81 is defined as the center of the field of view of the collection optics. The collection lens 74 is placed such that center line 80 extends through the center of lens 74.

Surface 54 is the object plane of collection lens 74. However, since the plane of surface 54 is not parallel to the longitudinal axis 78 of collection lens 74, the image plane of collection lens 74 (marked by a dotted line 82) is also not parallel to axis 78. This is known as the "Scheimpflug Condition" and it is described in the book Handbook of Optics, Vol. 1, McGraw-Hill, Inc., 1995, sections 1.66 and 1.67, whose disclosure is incorporated herein by reference. According to the Scheimpflug condition, the inclination angle  $\alpha$  of the image plane is defined by:

$$\tan \alpha = \frac{\tan \beta}{M}$$

where M is the lateral magnification of imaging system 52.

The photodetectors 76 are placed in the image plane 82 substantially near locations where the scan lines (not shown) of the scanned beams 70 are imaged. If the midpoints of the scan lines scanned by beams 70 are generally at a distance D from center point 81, then centers of photodetectors 76 are generally placed at distances MD from a point 84 where center line 80 intersects with image plane 82.

The distance 2D between the spots must be large enough to ensure that the residual light (as defined by the imaging demands) scattered from one spot does not enter the collection channels of the other spots. Typically, this condition requires the spots to be at least a multiple of the spot width apart.

5 Fig. 5 shows a wafer surface 54, as seen from the top, and a double scan, of areas 90A and 90B, thereon. Each scan 90 is formed by two orthogonal movements, labeled by arrows 92 and 94. Arrows 92 indicate the fast scan movement of scanned beams 70 as caused by the scan unit 58. Arrows 94 indicate scanning in the slow scan direction.

10 As discussed hereinabove, the spots must be separated. In the example of Fig. 5, the separation is the length 2L of two scan lines. Therefore, upon the completion of a scan, the two scan areas 90 have been viewed but the area 96 therebetween has not been scanned.

Other separations are possible, such as a separation of half the  
15 diameter of the wafer or such as separation within a scan line, and are incorporated in the present invention. If necessary, for system considerations such as the accuracy of a mechanical stage which moves the wafer, the scan lines may overlap. Preferably, the separation between two scan lines being scanned at the same time should be the length of at least two scan lines.

20 The output of the detectors 76 is processed as in the prior art. That is, the output signal is sampled at a rate corresponding to the spot size and to the velocity of the scanned beams 70 on the surface 54.

It will be appreciated that the present invention temporally separates pixels within each line, as in the prior art, and spatially separates scan lines, using the multiple beams and the multiple photodetectors.

It will further be appreciated that the present invention incorporates all  
5 collection lenses 74 which separate the light scattered from the spots so as to identify which light ray came from which spot and not just those which implement the Scheimpflug condition.

Reference is now made to Fig. 6 which shows an alternative embodiment of the collection lens of the present invention which limits the  
10 collected light to that which is scattered within a predetermined range of angles. This embodiment is useful for inspecting wafers which have a periodic pattern which scatters light in discrete angles. If this known scattered light is filtered out, any remaining scattered light must be due to errors in the wafer. Thus, this embodiment filters the known scattered light in order to view any undesired  
15 markings on the wafer.

In this embodiment, the collection optics include a spatial filter 100 in addition to the collection lens 74 and the photodetectors 76. Spatial filter 100 serves to limit the light arriving at the photodetectors 76 to be within a predefined range of angles of scattered light, such that the photodetectors 76  
20 view the same range of angles of scattered light during one scan. Spatial filter 100 can be implemented as an aperture stop or as a mask of any other desired shape so as to spatially filter the incoming light.

Fig. 6 indicates the possible angles of scattered light. The maximum angle of scattered light, labeled  $\beta_{\max}$ , occurs when the leftmost scanning beam

70A is at the beginning point, labeled 102, of its scan line, labeled 104. The minimum angle of scattered light, labeled  $\beta_{\min}$ , occurs when the rightmost scanning beam 70B is at the endpoint, labeled 108, of its scan line 106.

For a magnification of  $M=1$ , such as is shown in Fig. 6, the aperture  
5 stop 100 is placed one focal length beyond collection lens 74 and the image and object planes are two focal lengths from either side of the collection lens 74. The center of aperture stop 100 is aligned with center line 80 issuing at the center angle  $\beta_{\text{center}}$ . The aperture stop 100 has an aperture 110 which allows only that light which is scattered between  $\beta_{\max}$  and  $\beta_{\min}$  to pass through to  
10 photodetectors 76.

Other elements, such as polarization filters or wavelength filters, can be utilized to filter the light arriving at the photodetectors 76.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described  
15 herein above. Rather the scope of the invention is defined by the claims that follow:

**CLAIMS**

1. An inspection system using at least dark field imaging comprising:
  - a multiple beam laser scanning unit generating multiple beams which illuminate multiple spots on a surface to be scanned; and
  - 5 at least one multiple beam dark field imaging unit collecting light from at least one viewing perspective and separately detecting light scattered from said multiple spots.
2. An inspection system according to claim 1, wherein, for each viewing perspective, said imaging unit comprises:
  - 10 a plurality of photodetectors, at least one per spot, spaced apart from each other; and
  - collection optics directing light scattered from each spot to an assigned one of said photodetectors.
3. An inspection system according to claim 2 wherein said collection
- 15 optics and said photodetectors are arranged according to the principles of Scheimpflug imaging.
4. An inspection system according to claim 2 and wherein said collection optics additionally comprises a spatial filter for limiting the range of angles of scattered light which are received by said multiple
- 20 photodetectors.
5. An inspection system according to claim 2 and wherein said collection optics additionally comprises one of wavelength and polarization filters.
6. An inspection system according to claim 2 and wherein said multiple beams are separated by a separation distance which ensures that light

scattered from each associated spot is received only by its associated photodetector.

7. An inspection system according to claim 6 and wherein said separation distance is generally a multiple K of the length of a scan row  
5 less an overlap amount, where K is at least two.

8. An imaging unit according to claim 3 wherein a thin lens equivalent of said collection optics has a longitudinal axis, wherein said collection optics is mounted so that the longitudinal axis of said thin lens equivalent is at a first non-parallel angle to said surface, wherein said  
10 photodetectors are mounted along an image plane of said collection optics and wherein said image plane is at a second non-parallel angle to said longitudinal axis.

9. A multiple beam dark field imaging unit separately detecting light from multiple spots of a surface to be viewed, the imaging unit comprising:  
15 a plurality of photodetectors, at least one per spot, spaced apart from each other; and  
collection optics directing light scattered from each spot to an assigned one of said photodetectors.

10. An imaging unit according to claim 9 wherein said collection optics  
20 and said multiple photodetectors are arranged according to the principles of Scheimpflug imaging.

11. An imaging unit according to claim 9 wherein said collection optics additionally comprises a spatial filter for limiting the range of angles of scattered light which are received by said multiple photodetectors.



12. An inspection system according to claim 9 and wherein said collection optics additionally comprises one of wavelength and polarization filters.

13. An imaging unit according to claim 10 wherein a thin lens equivalent of said collection optics has a longitudinal axis, wherein said collection  
5 optics is mounted so that the longitudinal axis of said thin lens equivalent is at a first non-parallel angle to said surface, wherein said photodetectors are mounted along an image plane of said collection optics and wherein said image plane is at a second non-parallel angle to said longitudinal axis.


10 14. An inspection system using dark field imaging, the system comprising:

a source generating a plurality of light beams;


a scanner simultaneously scanning said light beams over a plurality of respective scan lines; and

15 a sensor system collecting scattered light, spatially separating between the multiple scan lines and temporally separating pixels within said multiple scan lines.


1/5



FIG. 1  
PRIOR ART

2/5

FIG. 2  
PRIOR ART

3/5

FIG. 3  
PRIOR ART






FIG. 6

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 98/23348

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G01N21/88

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 22520 A (PHOTON DYNAMICS INC) 25 July 1996	9
A	see page 15, line 6 - page 16, line 5; figure 7	1, 14
A	WO 97 46865 A (TENCOR INSTRUMENTS) 11 December 1997 see page 8, line 15 - page 13, line 4; claim 1; figure 1	1, 9, 14
A	US 4 013 367 A (NAGAO YUKIO ET AL) 22 March 1977 see abstract; figure 1	1, 9, 14
A	DE 43 04 815 A (LEITZ MESTECHNIK GMBH) 18 August 1994 see abstract; figure 1	1, 3, 9, 10, 14
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

16 February 1999

Date of mailing of the international search report

23/02/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Tabellion, M

# INTERNATIONAL SEARCH REPORT

In ☐ International Application No  
PCT/US 98/23348

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 641 020 A (APPLIED MATERIALS INC) 1 March 1995	
A	WO 94 09989 A (ETEC SYSTEMS INC) 11 May 1994	



# INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/US 98/23348

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9622520 A	25-07-1996	US 5631733 A	20-05-1997
WO 9746865 A	11-12-1997	AU 3376597 A	05-01-1998
US 4013367 A	22-03-1977	JP 918418 C	15-08-1978
		JP 50145290 A	21-11-1975
		JP 52048031 B	07-12-1977
		DE 2521037 A	27-11-1975
DE 4304815 A	18-08-1994	NONE	
EP 0641020 A	01-03-1995	US 5422724 A	06-06-1995
		JP 7193109 A	28-07-1995
WO 9409989 A	11-05-1994	US 5386221 A	31-01-1995
		AU 5410394 A	24-05-1994
		CA 2148122 A	11-05-1994
		DE 811882 T	22-10-1998
		EP 0670784 A	13-09-1995
		EP 0811882 A	10-12-1997
		JP 8507410 T	06-08-1996

